

AIRCRAFT HYDRAULIC FLUID REMOVER

PART # 35391A4

PRODUCT DESCRIPTION

Aircraft Hydraulic Fluid Remover (AHFR) is a mix-blend cleaner base on fatty ester and designed to easily remove hydraulic fluid. AHFR has been tested and approved for AMS - 1526B specifications by SMI Inc, Miami, USA.

ADVANTAGES

- Non-toxic
- Non-flammable
- No phosphates
- High biodegradability (tested by the University of Ghent, Belgium)
- Classified as a non-dangerous preparation.
- Not subject to dangerous goods regulations.
- Quickly de-emulsifies, resulting in an excellent separation of oil and water

APPLICATIONS

AHFR is specially formulated to remove sticky hydraulic oil deposits from aircraft fuselages, wheel and landing gear areas. AHFR also removes various types of oils and greases and hydrocarbon deposits. AHFR is environmentally benign and replaces chlorinated products and solvent based cleaners. AHFR is a ready for use product and may also be used as a spot cleaner on aircraft.

DIRECTIONS FOR USE

- Spray the product on the surface to be cleaned
- Depending from the thickness of the hydraulic oil layer, let the product work for 1 to max 15 minutes.
- Rinse off with water

It is recommended to re-treat the complete aircraft afterwards with Ecosterile Aircraft Cleaner. This product will create an antistatic layer on the fuse lage and reduce the adherence of hydraulic oil deposits in the future.

PACKAGING 1 Ltr.; 5 Ltr., 25 Ltr., 250 Ltr. :

SHELLLIFE 4years

STORAGE Do not store under 35°F/2°C and not above 122°F/50°C Do not use below 35°F/2°C.